LED Strip Lights



INTRODUCTION

Features:

- 1.Super-bright, Low power consumption of SMD LED
- 2. Linear separable LED strip light on the flexible PCB with self-adhesive back
- 3. Energy Saving, Long lifespan of SMD LED (>50, 000hours)
- 4. Each unit of 3 LEDs can be cut out at regular segments without damaging the rest ribbon.
- 5. Use ultra-thin and flexible PCB, the thickness for non-waterproof is 2.2mm and thickness for waterproof is 3.4mm


Applications:

- 1. Car decoration
- 2. Architectural decorative lighting
- 3. Archway, canopy and bridge edge lighting
- 4. Amusement park
- 5. Emergency hallway lighting
- 6. Auditorium walkway lighting
- 7. Stairway accent lighting
- 8. Channel letter lighting



GN - FSP-1210UWC-300- WP-A

NAMING RULES






SPECIFICATIONS

Light source parameters	
LED type	SMD 1210
Angle(⊕)	120°
LED Qty	300PCS
Life Span	>50,000 hours
Electrical parameters	
Luminous flux(lm)	320lm/m
Voltage	12VDC
Power	4.3w/m

Appearance parameters	
Size	8mm*5000mm
LED Color	CW/WW/R/G/B/Y
Fixed way	3M
Environmental parameters	
Working Temperature	-20 °C− +50 °C
Storage Temperature	-30°C- +60°C
waterproof	IP65
Warranty	24Months

SIZE



PACKING INFORMATION



Electrostatic bag size	200*260mm
Outside packing carton	225*265*115mm
Packing Qty	10PCS
Net weight	2kg/1Box
Gross weight	2.2kg