LED Strip Lights



INTRODUCTION

Features:

- 1.Super-bright, Low power consumption of SMD LED
- 2. Linear separable LED strip light on the flexible PCB with self-adhesive back
- 3. Energy Saving, Long lifespan of SMD LED (>50, 000hours)
- 4. Each unit of 3 LEDs can be cut out at regular segments without damaging the rest ribbon.
- 5. Use ultra-thin and flexible PCB, the thickness for non-waterproof is 2.2mm and thickness for waterproof is 3.4mm

Applications:


- 1. Car decoration
- 2. Architectural decorative lighting
- 3. Archway, canopy and bridge edge lighting
- 4. Amusement park
- 5. Emergency hallway lighting
- 6. Auditorium walkway lighting
- 7. Stairway accent lighting
- 8. Channel letter lighting





GN - FSP-1210UWC-600--A

NAMING RULES





SPECIFICATIONS

| Light source parameters | |
|-------------------------|---------------|
| LED type | SMD 1210 |
| Angle(⊕) | 120° |
| LED Qty | 600PCS |
| Life Span | >50,000 hours |
| Electrical parameters | |
| Luminous flux(lm) | 640lm/m |
| Voltage | 12VDC |
| Power | 8.6w/m |
| | |

| Appearance parameters | |
|--------------------------|---|
| Size | 8mm*5000mm |
| ED Color | CW/WW/R/G/B/Y |
| Fixed way | 3M |
| Environmental parameters | |
| Working emperature | -20 °C - +50 °C |
| Storage `emperature | -30 °C - +60 °C |
| waterproof | IP65 |
| Warranty | 24Months |
| | Size ED Color Fixed way Enviro Working emperature Storage emperature waterproof |

SIZE



Units:Millimeters

PACKING INFORMATION



| Electrostatic bag size | 200*260mm |
|------------------------|------------------|
| Outside packing carton | 225*265*115mm |
| Outside packing carton | 223 203 11311111 |
| Packing Qty | 10PCS |
| Net weight | 1.4kg/1Box |
| Gross weight | 1.6kg |